



OFFICIAL LISTING

NSF Certifies that the products appearing on this Listing conform to the requirements of
NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on October 15, 2025.

KeenSen Technology Co., Ltd.
No. 370, Minghu Road
Yuelu District
Hunan
China
86 731 8997 2869

Facility: Hunan, China

Mechanical Devices

Trade Name	Size	Water Contact Temp	Water Contact Material
Reverse Osmosis Element [1] [2] [3]			
ACR-8040	8" x 40"	CLD 23	MLTPL
ALR-8040	8" x 40"	CLD 23	MLTPL
AWT-4021	4" x 21"	CLD 23	MLTPL
BW-2521	2 1/2" x 21"	CLD 23	MLTPL
BW-2521FR	2 1/2" x 21"	CLD 23	MLTPL
BW-2540	2 1/2" x 40"	CLD 23	MLTPL
BW-2540FR	2 1/2" x 40"	CLD 23	MLTPL
BW-4021	4" x 21"	CLD 23	MLTPL
BW-4021FR	4" x 21"	CLD 23	MLTPL
BW-4040	4" x 40"	CLD 23	MLTPL
BW-4040-2	4" x 40"	CLD 23	MLTPL
BW-4040-E	4" x 40"	CLD 23	MLTPL
BW-4040FR	4" x 40"	CLD 23	MLTPL
BW-4040HF	4" x 40"	CLD 23	MLTPL
BW-4040XLFR	4" x 40"	CLD 23	MLTPL
BW-8040	8" x 40"	CLD 23	MLTPL
BW-8040-2	8" x 40"	CLD 23	MLTPL
BW-8040-E	8" x 40"	CLD 23	MLTPL
BW-8040FR	8" x 40"	CLD 23	MLTPL
BW-8040FR-2	8" x 40"	CLD 23	MLTPL

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



BW-8040HF	8" x 40"	CLD 23	MLTPL
BW-8040LFR	8" x 40"	CLD 23	MLTPL
BW-8040MR	8" x 40"	CLD 23	MLTPL
BW-8040MXFR	8" x 40"	CLD 23	MLTPL
BW-8040XLFR	8" x 40"	CLD 23	MLTPL
EP-4040LE	4" x 40"	CLD 23	MLTPL
EP-8040FR	8" x 40"	CLD 23	MLTPL
EP-8040HRLE	8" x 40"	CLD 23	MLTPL
EP-8040XLFR	8" x 40"	CLD 23	MLTPL
ES-4040HF	4" x 40"	CLD 23	MLTPL
ES-4040HR	4" x 40"	CLD 23	MLTPL
ES-4040UFR	4" x 40"	CLD 23	MLTPL
ES-8040HF	8" x 40"	CLD 23	MLTPL
ES-8040HR	8" x 40"	CLD 23	MLTPL
ES-8040UFR	8" x 40"	CLD 23	MLTPL
HES-8040	8" x 40"	CLD 23	MLTPL
HP-8040	8" x 40"	CLD 23	MLTPL
HW-8040	8" x 40"	CLD 23	MLTPL
MS-8040H	8" x 40"	CLD 23	MLTPL
MS-8040L	8" x 40"	CLD 23	MLTPL
MS-8040M	8" x 40"	CLD 23	MLTPL
MTW-8040HF	8" x 40"	CLD 23	MLTPL
MTW-8040HR	8" x 40"	CLD 23	MLTPL
SOR-8040	8" x 40"	CLD 23	MLTPL
SU-8040LE	8" x 40"	CLD 23	MLTPL
SU-8040XLE	8" x 40"	CLD 23	MLTPL
SW-2521	2 1/2" x 21"	CLD 23	MLTPL
SW-2540	2 1/2" x 40"	CLD 23	MLTPL
SW-4021	4" x 21"	CLD 23	MLTPL
SW-4040	4" x 40"	CLD 23	MLTPL
SW-4040HF	4" x 40"	CLD 23	MLTPL
SW-4040HR	4" x 40"	CLD 23	MLTPL
SW-4040MR	4" x 40"	CLD 23	MLTPL
SW-8040	8" x 40"	CLD 23	MLTPL
SW-8040HF	8" x 40"	CLD 23	MLTPL
SW-8040HR	8" x 40"	CLD 23	MLTPL
SW-8040MR	8" x 40"	CLD 23	MLTPL
SW-8040MR-2	8" x 40"	CLD 23	MLTPL
SW-8040SHF	8" x 40"	CLD 23	MLTPL
SW-8040XHR	8" x 40"	CLD 23	MLTPL
UHP-8040P120	8" x 40"	CLD 23	MLTPL

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



UHP-8040P70	8" x 40"	CLD 23	MLTPL
ULP-2521	2 1/2" x 21"	CLD 23	MLTPL
ULP-2540	2 1/2" x 40"	CLD 23	MLTPL
ULP-4021	4" x 21"	CLD 23	MLTPL
ULP-4021HR	4" x 21"	CLD 23	MLTPL
ULP-4040	4" x 40"	CLD 23	MLTPL
ULP-4040-2	4" x 40"	CLD 23	MLTPL
ULP-4040HF	4" x 40"	CLD 23	MLTPL
ULP-4040HR	4" x 40"	CLD 23	MLTPL
ULP-4040MR	4" x 40"	CLD 23	MLTPL
ULP-4040MR-2	4" x 40"	CLD 23	MLTPL
ULP-8040	8" x 40"	CLD 23	MLTPL
ULP-8040-2	8" x 40"	CLD 23	MLTPL
ULP-8040HF	8" x 40"	CLD 23	MLTPL
ULP-8040MR-2	8" x 40"	CLD 23	MLTPL
XLP-2521	2 1/2" x 21"	CLD 23	MLTPL
XLP-2540	2 1/2" x 40"	CLD 23	MLTPL
XLP-4021	4" x 21"	CLD 23	MLTPL
XLP-4040	4" x 40"	CLD 23	MLTPL
XLP-4040HF	4" x 40"	CLD 23	MLTPL
XLP-8040	8" x 40"	CLD 23	MLTPL
XLP-8040HF	8" x 40"	CLD 23	MLTPL
ZM-8040FL	8" x 40"	CLD 23	MLTPL
ZM-8040FR	8" x 40"	CLD 23	MLTPL
ZM-8040HP	8" x 40"	CLD 23	MLTPL
ZM-8040UHF	8" x 40"	CLD 23	MLTPL
ZM-8040UHP	8" x 40"	CLD 23	MLTPL

[1] Size is expressed as Diameter x length.

[2] ACR-8040, ALR-8040 models are certified for a minimum daily flow of 10000 gallons.
AWT-4021 model is certified for a minimum daily flow of 1400 gallons.
BW-2521, ULP-2521 models are certified for a minimum daily flow of 400 gallons.
HW-8040 model is certified for a minimum daily flow of 8,500 gallons.
BW-2540FR model is certified for a minimum daily flow of 600 gallons.
BW-4040, BW-4040-E models are certified for a minimum daily flow of 2,400 gallons.
BW-4040-2 model is certified for a minimum daily flow of 2,300 gallons.
BW-4040HF model is certified for a minimum daily flow of 2,900 gallons.
BW-4040XLFR model is certified for a minimum daily flow of 2,300 gallons.
BW-8040, ULP-8040 models are certified for a minimum daily flow of 10,000 gallons.
BW-8040HF, XLP-8040HF models are certified for a minimum daily flow of 13,000 gallons.
BW-8040MR, BW-8040FR models are certified for a minimum daily flow of 9,500 gallons.
BW-8040MXFR model is certified for a minimum daily flow of 11,500 gallons.
BW-8040XLFR model is certified for a minimum daily flow of 11,500 gallons.
BW-8040LFR, BW-8040-2, ULP-8040MR-2, BW-8040-E, BW-8040FR-2, ES-8040UFR models are Certified for a minimum daily flow of 10,500 gallons.
EP-8040HRLE is certified for a minimum daily flow of 10400 gallons.
EP-8040XLFR and SW-8040SHF are certified for a minimum daily flow of 8400 gallons.
ES-8040HF, MTW-8040HF model is certified for a minimum daily flow of 12000 gallons.
HES-8040 and SOR-8040 are certified for a minimum daily flow of 7000 gallons.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



HP-8040, ZM-8040UHP and ZM-8040FL are certified for a minimum daily flow of 6500 gallons.
MTW-8040HR, MS-8040H models are certified for a minimum daily flow of 8000 gallons.
MS-8040L model is certified for a minimum daily flow of 10000 gallons.
SU-8040LE and SU-8040XLE are certified for a minimum daily flow of 9500 gallons.
SW-2521, BW-2521FR models are certified for a minimum daily flow of 250 gallons.
SW-2540 model is certified for a minimum daily flow of 500 gallons.
SW-4021 model is certified for a minimum daily flow of 700 gallons.
SW-4040, BW-4040FR models are certified for a minimum daily flow of 2,000 gallons.
SW-4040HF is certified for a minimum daily flow of 1600 gallons.
SW-4040HR model is certified for a minimum daily flow of 1,500 gallons.
SW-8040, MS-8040M models are certified for a minimum daily flow of 9,000 gallons.
SW-8040 model is certified for a minimum daily flow of 9,000 gallons.
SW-8040HF model is certified for a minimum daily flow of 9000 gallons.
SW-8040HR model is certified for a minimum daily flow of 6,500 gallons.
SW-8040MR model is certified for a minimum daily flow of 7,500 gallons.
SW-8040XHR model is certified for a minimum daily flow of 7000 gallons.
UHP-8040P120 is certified for a minimum daily flow of 8500 gallons.
UHP-8040P70 is certified for a minimum daily flow of 5500 gallons.
ULP-2540 model is certified for a minimum daily flow of 750 gallons.
ULP-4021 model is certified for a minimum daily flow of 950 gallons.
ULP-4021HR is certified for a minimum daily flow of 640 gallons.
ULP-4040 model is certified for a minimum daily flow of 2,600 gallons.
ULP-4040-2 model is certified for a minimum daily flow of 2,200 gallons.
ULP-4040HF model is certified for a minimum daily flow of 2,700 gallons.
ULP-4040HR, SW-4040MR models are certified for a minimum daily flow of 1,800 gallons.
ULP-4040MR model is certified for a minimum daily flow of 2,200 gallons.
ULP-8040HF model is certified for a minimum daily flow of 12,500 gallons.
XLP-2521 model is certified for a minimum daily flow of 400 gallons.
XLP-2540, BW-2540, BW-4021FR models are certified for a minimum daily flow of 750 gallons.
XLP-4021, BW-4021 models are certified for a minimum daily flow of 950 gallons.
XLP-8040, ULP-8040 models are certified for a minimum daily flow of 11,000 gallons.
ULP-8040-2, MS-8040L model is certified for a minimum daily flow of 10,000 gallons.
ULP-4040MR, ES-4040UFR models are certified for

- [3] All models 2.5" in diameter require a 2 gpm flush for 24 hours using tap water.
All models 4" in diameter require a 4 gpm flush for 24 hours using tap water.
All models 8" in diameter require a 15 gpm flush for 24 hours using tap water.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.